


How to Order



Series compatible with secondary batteries

- Option/Semi-standard: Select one each for a to c.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
- Example) 25A-AF30-N03B-RZ-A

				0				
			Description	Body size				
				20	30	40	50	60
	Pipe thread type	Nil	Rc	•	•	•	•	•
2		N	NPT	•	•	•	•	•
		F	G	•	•	•	•	•
		+						
	Port size	01	1/8	•	_	_	_	_
		02	1/4	•	•	•	_	_
8		03	3/8	_		•	_	_
		04	1/2	_	_	•	_	_
		06	3/4	_	_	•	•	_
		10	1	_	_	_	•	
		+						
4	a Mounting	Nil	Without mounting option	•	•	•	•	•
		B*1	With bracket					
		+						
	D b Flow direction	Nil	Flow direction: Left to right		•	•	•	
	E B 1 low direction	R	Flow direction: Right to left			•	•	
6	-sta	+						
	b Flow direction c Pressure unit	Nil	Name plate and caution plate for bowl in SI units: MPa		•	•	•	•
		Z *2	Name plate and caution plate for bowl in imperial units: psi, °F	O*2	O*2	O*2	O*2	O*2

- *1 A bracket is not assembled and supplied loose at the time of shipment. Including 2 mounting screws.
- *2 O: For pipe thread type: NPT. This product is for overseas use only according to the New Measurement Law. (The SI unit type is provided for use in Japan.)
 - * The 25A- series specifications and dimensions are the same as those of the standard model.

Click here for details.

Bracket, Bowl Assembly Part Nos. for the 25A- Series

Model Option	25A-AF20-A	25A-AF30-A	25A-AF40-A	25A-AF40-06-A	25A-AF50-A 25A-AF60-A
Bracket assembly*1	25A-AF22P-050AS	25A-AF32P-050AS	25A-AF42P-050AS	25A-AF42P-070AS	25A-AF52P-050AS
Bowl assembly	25A-C2SF-A	25A-C3SF-A		25A-C4SF-A	

^{*1} Assembly of a bracket and 2 mounting screws.

Air Cylinders Control Valves

Related Products

Rotary Actuators

Air Grippers

Fluid Control Equipment

Electric Actuators

Auto Switches

160