Regulator


25A-AR20-B to 25A-AR60-B

Regulator with Backflow Function

25A-AR20K-B to 25A-AR60K-B



How to Order



- Option/Semi-standard: Select one each for a to f.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order. Example) 25A-AR30K-03B-1NR-B

						0					
	Sy			Description	Body size						
					2	20	25	30	40	50	60
	Wit	h backflow	Nil	Without backflow function			•	•	•	•	•
	1	function	K	With backflow function			•	•	•	•	•
			+								
			Nil	Rc			•			•	•
)	Pipe	e thread type	N	NPT			•	•	•	•	•
			F	G			•	•	•	•	•
			+								
				1/8			_	_	_	_	_
			02	1/4			•	•	•	_	_
F		Port size	03	3/8		_	•	•	•	_	_
	·	FUIT SIZE		1/2		_	_	_	•	_	_
			06 10	3/4			_	_	•	•	_
				1			_	_	_		•
			+								
Ontion	a Mounting		Nil	Without mounting option			•			•	•
		B *2	With bracket			•	•		•	•	
ြင်	5		Н	With set nut (For panel fitting)			•	•	•	_	_
			+								
		h Cat avaaavus	Nil	0.05 to 0.85 MPa setting			•				
	b Set press	Set pressure	1 *3	0.02 to 0.2 MPa setting			•	•		•	•
			+	•							
5	c	Exhaust mechanism	Nil	Relieving type			•	•		•	
			N	Non-relieving type			•	•	•	•	Ī
100	g		+	<u> </u>							
Semi-standard		Flow direction	Nil	Flow direction: Left to right			•				•
	g d		R	Flow direction: Right to left			Ŏ				ě
3			+								
Se	3	., .	Nil	Downward			•		•	•	
	´ e	Knob	Y	Upward			-				
			+	- P. 1. 2. 2		_				_	
			Nil	Name plate in SI units: MPa							
	f	Pressure unit	Z *4	Name plate in imperial units: psi	-+)*4	O*4	O*4	O*4	O*4	Ö

- *1 Option "B", "H" are not assembled and supplied loose at the time of shipment.
- *2 Assembly of a bracket and set nuts (25A-AR20(K) to 25A-AR40(K)). Including 2 mounting screws for the 25A-AR50(K) and 25A-AR60(K).
- *3 Pressure can be set at the upper limit of the specification or more, however, be sure to set the pressure within specification.
- *4 O: For pipe thread type: NPT. This product is for overseas use only according to the New Measurement Law. (The SI unit type is provided for use in Japan.)

* The 25A- series specifications and dimensions are the same as those of the standard model.

Click here for details.

Bracket, Set Nut Part Nos. for the 25A- Series

Model Option	25A-AR20(K)-B	25A-AR25(K)-B	25A-AR30(K)-B	25A-AR40(K)-B	25A-AR50(K)-B 25A-AR60(K)-B
Bracket assembly*1	25A-AR23P-270AS	25A-AR28P-270AS	25A-AR33P-270AS	25A-AR43P-270AS	25A-AR52P-270AS*2
Set nut	AR23P-260S	AR28P-260S	AR33P-260S	AR43P-260S	*3

- *1 Assembly of a bracket and set nuts.
- *2 Assembly of a bracket and 2 mounting screws.
- *3 Please consult with SMC regarding the set nuts for the 25A-AR50(K) and 25A-AR60(K).



162

Directional Control Valves

Air Cylinders

Related Products

Rotary Actuators

Air Grippers Vacuum Equipment

Air Preparation Equipment

Control Equipment

Detection Switches

Fluid Control Equipment

Electric Actuators

Switches