


# Compact Guide Cylinder MGQ Series

ø12, ø16, ø20, ø25, ø32, ø40, ø50, ø63, ø80, ø100

## How to Order



### Applicable Auto Switches/Refer to pages 1119 to 1245 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length (m)				Pre-wired connector	Applicable load			
					DC	AC	Perpendicular	In-line	0.5 (Nil)	1 (M)	3 (L)	5 (Z)					
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9NV	M9N	●	●	●	○	○	IC circuit	Relay, PLC	
				3-wire (PNP)				M9PV	M9P	●	●	●	○	○			
				2-wire				M9BV	M9B	●	●	●	○	○			
				3-wire (NPN)				M9NWV	M9NW	●	●	●	○	○			
	Diagnostic indication (2-color indicator)			3-wire (PNP)	M9PWV	M9PW	●	●	●	○	○	○	○	○	○		IC circuit
				2-wire	M9B WV	M9B W	●	●	●	○	○	○	○	○	○		—
				3-wire (NPN)	M9NAV*1	M9NA*1	○	○	●	○	○	○	○	○	○		IC circuit
				3-wire (PNP)	M9PAV*1	M9PA*1	○	○	●	○	○	○	○	○	○		IC circuit
Water resistant (2-color indicator)	2-wire	M9BAV*1	M9BA*1	○	○	●	○	○	○	○	○	○	—				
	Reed auto switch	Grommet	No	3-wire (NPN equivalent)	24 V	5 V	—	A96V	A96	●	—	●	—	—	IC circuit	—	
				2-wire				100 V	12 V	100 V or less	A93V*2	A93	●	●	●	●	—
	A90V	A90	●	—	●	—	—				—	—	—	IC circuit	PLC		

\*1 Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance. Consult with SMC regarding water resistant types with the above model numbers.

\*2 1 m type lead wire is only applicable to D-A93.

\* Lead wire length symbols: 0.5 m ..... Nil (Example) M9NW  
 1 m ..... M (Example) M9NWM  
 3 m ..... L (Example) M9NWL  
 5 m ..... Z (Example) M9NWZ

\* Solid state auto switches marked with "○" are produced upon receipt of order.

\* Since there are other applicable auto switches than listed, refer to page 531 for details.  
 \* For details about auto switches with pre-wired connector, refer to pages 1192 and 1193.  
 \* Auto switches are shipped together (not assembled).

**Air cylinder integrated with guide has achieved anti-lateral load and high non-rotating accuracy.**

**Space-saving and compact design**


**Suitable as stoppers or lifters in conveyor line**

**2 types of guide rod bearing are available depending upon the application**

Slide bearing/Ball bushing bearing



**Symbol**  
Rubber bumper



**Made to Order: Individual Specifications**  
(For details, refer to pages 532 and 533.)

Symbol	Specifications
-X168	Helical insert thread
-X367	Bottom mounting type
-X399	Long bushing type
-X563	With anti-strong magnetic field switch (D-P4DW)

### Made to Order Specifications

[Click here for details](#)

Symbol	Specifications
-XA□	Change of rod end shape
-XB6	Heat resistant cylinder (-10 to 150°C)
-XB9	Low speed cylinder (10 to 50 mm/s)
-XB10	Intermediate stroke (Using exclusive body)
-XC22	Fluororubber seals
-XC56	With knock pin holes
-XC79	Machining tapped hole, drilled hole, and pin hole additionally


### Specifications

Bearing type	Slide bearing		Ball bushing bearing	
	MGQM		MGQL	
Model				
Bore size (mm)	12, 16, 20, 25, 32, 40, 50, 63, 80, 100			
Action	Double acting			
Fluid	Air			
Proof pressure	1.5 MPa			
Max. operating pressure	1.0 MPa			
Min. operating pressure	ø12, ø16	0.12 MPa		
	ø20 to ø100	0.1 MPa		
Ambient and fluid temperature	-10 to 60°C (No freezing)			
Piston speed	ø12 to ø63	50 to 500 mm/s		
	ø80, ø100	50 to 400 mm/s		
Cushion	Rubber bumper on both ends			
Lubrication	Non-lube			
Stroke length tolerance	+1.5 0 mm			

### Standard Stroke

Model	Standard stroke (mm)	Intermediate stroke (mm)
MGQ <sup>M</sup> <sub>L</sub> 12, 16	10, 20, 30, 40, 50, 75, 100	As for the intermediate strokes other than the standard strokes at left are manufactured by means of installing a spacer. ø12 to ø32 ..... Stroke available in 1 stroke increments ø40 to ø100 ..... Stroke available in 5 stroke increments (Example) 1. For MGQM20-21 st, MGQM20-30 st is provided with a 5 mm + 4 mm ≤ 9 mm width spacer. 2. For MGQM50-40 st, MGQM50-50 st is provided with a 10 mm width spacer.
MGQ <sup>M</sup> <sub>L</sub> 20, 25	20, 30, 40, 50, 75, 100 125, 150, 175, 200	
MGQ <sup>M</sup> <sub>L</sub> 32, 40 50, 63 80, 100	25, 50, 75, 100, 125 150, 175, 200	

### Theoretical Output



Bore size (mm)	Rod size (mm)	Operating direction	Piston area (mm <sup>2</sup> )	Operating pressure (MPa)									
				0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
12	6	OUT	113	23	34	45	57	68	79	90	102	113	
		IN	85	17	26	34	43	51	60	68	77	85	
16	8	OUT	201	40	60	80	101	121	141	161	181	201	
		IN	151	30	45	60	76	91	106	121	136	151	
20	10	OUT	314	63	94	126	157	188	220	251	283	314	
		IN	236	47	71	94	118	142	165	189	212	236	
25	12	OUT	491	98	147	196	246	295	344	393	442	491	
		IN	378	76	113	151	189	227	265	302	340	378	
32	16	OUT	804	161	241	322	402	482	563	643	724	804	
		IN	603	121	181	241	302	362	422	482	543	603	
40	16	OUT	1257	251	377	503	629	754	880	1006	1131	1257	
		IN	1056	211	317	422	528	634	739	845	950	1056	
50	20	OUT	1963	393	589	785	982	1178	1374	1570	1767	1963	
		IN	1649	330	495	660	825	990	1154	1319	1484	1649	
63	20	OUT	3117	623	935	1247	1559	1870	2182	2494	2805	3117	
		IN	2803	561	841	1121	1402	1682	1962	2242	2523	2803	
80	25	OUT	5027	1005	1508	2011	2514	3016	3519	4022	4524	5027	
		IN	4536	907	1361	1814	2268	2722	3175	3629	4082	4536	
100	30	OUT	7854	1571	2356	3142	3927	4712	5498	6283	7069	7854	
		IN	7147	1429	2144	2859	3574	4288	5003	5718	6432	7147	

Note) Theoretical output (N) = Pressure (MPa) x Piston area (mm<sup>2</sup>)

MGJ

JMGP

MGP

MGPW

MGQ

MGG

MGC

MGF

MGZ

MGT

D-□

-X□

# MGQ Series

## Weight/Slide Bearing: MGQM12 to 100

(kg)

Bore size (mm)	Model	Standard stroke (mm)											
		10	20	25	30	40	50	75	100	125	150	175	200
12	MGQM12	0.23	0.27	—	0.31	0.34	0.38	0.48	0.58	—	—	—	—
16	MGQM16	0.34	0.39	—	0.45	0.50	0.55	0.68	0.80	—	—	—	—
20	MGQM20	—	0.54	—	0.61	0.69	0.76	0.94	1.09	1.24	1.39	1.54	1.69
25	MGQM25	—	0.83	—	0.93	1.04	1.13	1.44	1.68	1.92	2.16	2.40	2.64
32	MGQM32	—	—	1.51	—	—	1.91	2.29	2.69	3.09	3.49	3.89	4.29
40	MGQM40	—	—	1.65	—	—	2.24	2.46	2.87	3.28	3.69	4.10	4.51
50	MGQM50	—	—	2.54	—	—	3.09	3.65	4.21	4.77	5.33	5.89	6.45
63	MGQM63	—	—	3.01	—	—	3.63	4.23	4.85	5.47	6.09	6.71	7.33
80	MGQM80	—	—	5.66	—	—	6.59	7.49	8.41	9.33	10.25	11.17	12.09
100	MGQM100	—	—	8.96	—	—	10.27	11.57	12.90	14.23	15.56	16.89	18.22


## Weight/Ball Bushing Bearing: MGQL12 to 100

(kg)

Bore size (mm)	Model	Standard stroke (mm)											
		10	20	25	30	40	50	75	100	125	150	175	200
12	MGQL12	0.23	0.26	—	0.29	0.35	0.38	0.46	0.53	—	—	—	—
16	MGQL16	0.35	0.39	—	0.44	0.52	0.57	0.70	0.82	—	—	—	—
20	MGQL20	—	0.54	—	0.60	0.70	0.75	0.90	1.04	1.18	1.32	1.46	1.60
25	MGQL25	—	0.84	—	0.93	1.08	1.17	1.37	1.58	1.79	2.00	2.21	2.42
32	MGQL32	—	—	1.32	—	—	1.67	2.09	2.45	2.81	3.17	3.53	3.89
40	MGQL40	—	—	1.46	—	—	1.82	2.27	2.63	2.99	3.35	3.71	4.07
50	MGQL50	—	—	2.11	—	—	2.59	3.19	3.68	4.17	4.66	5.15	5.64
63	MGQL63	—	—	2.65	—	—	3.19	3.85	4.39	4.93	5.47	6.01	6.55
80	MGQL80	—	—	5.49	—	—	6.38	7.95	8.79	9.63	10.47	11.31	12.15
100	MGQL100	—	—	8.34	—	—	9.53	11.78	12.96	14.14	15.32	16.50	17.68


**Operating Conditions**

**Allowable Lateral Load (Ordinary load)**



Bore size (mm)	Bearing type	Stroke (mm)											F(N)
		10	20	25	30	40	50	75	100	125	150	175	
12	MGQM	21	18	—	15	13	12	9	8	—	—	—	—
	MGQL	27	22	—	17	21	19	15	13	—	—	—	—
16	MGQM	34	28	—	25	22	19	15	13	—	—	—	—
	MGQL	38	30	—	26	37	33	28	23	—	—	—	—
20	MGQM	—	51	—	44	38	34	57	49	42	37	33	30
	MGQL	—	55	—	47	78	69	53	44	30	26	23	21
25	MGQM	—	70	—	60	53	47	77	65	56	49	44	40
	MGQL	—	71	—	61	77	72	59	51	42	36	32	29
32	MGQM	—	—	196	—	—	167	137	108	87	77	69	63
	MGQL	—	—	88	—	—	59	275	216	156	136	121	109
40	MGQM	—	—	196	—	—	167	137	108	87	77	69	63
	MGQL	—	—	88	—	—	59	275	216	156	136	121	109
50	MGQM	—	—	294	—	—	255	215	176	138	123	111	101
	MGQL	—	—	137	—	—	88	392	313	207	182	162	146
63	MGQM	—	—	294	—	—	255	215	176	138	123	111	101
	MGQL	—	—	137	—	—	88	392	313	207	182	162	146
80	MGQM	—	—	353	—	—	304	255	206	168	151	137	126
	MGQL	—	—	235	—	—	157	863	686	465	411	368	333
100	MGQM	—	—	539	—	—	470	412	343	278	252	230	211
	MGQL	—	—	470	—	—	313	1370	1070	708	627	562	509


**Allowable Rotational Torque of Plate**



Bore size (mm)	Bearing type	Stroke (mm)											T (N-m)
		10	20	25	30	40	50	75	100	125	150	175	
12	MGQM	0.29	0.24	—	0.21	0.18	0.16	0.13	0.10	—	—	—	—
	MGQL	0.48	0.39	—	0.31	0.37	0.33	0.27	0.23	—	—	—	—
16	MGQM	0.51	0.43	—	0.35	0.31	0.27	0.23	0.19	—	—	—	—
	MGQL	0.73	0.58	—	0.48	0.71	0.64	0.53	0.44	—	—	—	—
20	MGQM	—	0.91	—	0.78	0.71	0.63	1.04	0.88	0.77	0.68	0.60	0.55
	MGQL	—	1.26	—	1.06	1.77	1.58	1.22	1.01	0.69	0.60	0.53	0.48
25	MGQM	—	1.53	—	1.31	1.16	1.03	1.68	1.42	1.24	1.09	0.98	0.88
	MGQL	—	1.96	—	1.69	2.16	2.00	1.65	1.41	1.18	1.01	0.90	0.81
32	MGQM	—	—	3.92	—	—	2.94	2.45	3.46	1.72	1.53	1.37	1.24
	MGQL	—	—	1.96	—	—	0.98	5.88	4.41	3.12	2.72	2.42	2.18
40	MGQM	—	—	4.41	—	—	3.43	2.94	2.45	1.94	1.72	1.54	1.40
	MGQL	—	—	2.45	—	—	1.47	6.37	5.39	3.51	3.06	2.72	2.45
50	MGQM	—	—	7.35	—	—	5.88	4.90	4.41	3.43	3.06	2.77	2.52
	MGQL	—	—	3.43	—	—	2.20	10.78	8.33	5.18	4.55	4.05	3.65
63	MGQM	—	—	7.84	—	—	6.37	5.39	4.90	3.77	3.37	3.04	2.77
	MGQL	—	—	3.92	—	—	2.45	11.76	9.31	5.69	5.01	4.46	4.02
80	MGQM	—	—	11.76	—	—	9.80	7.84	6.86	5.88	5.28	4.79	4.39
	MGQL	—	—	9.31	—	—	5.88	31.36	24.50	16.28	14.39	12.88	11.66
100	MGQM	—	—	22.54	—	—	19.60	16.66	14.70	11.81	10.67	9.74	8.96
	MGQL	—	—	21.56	—	—	13.72	63.70	49.00	30.09	26.65	23.89	21.63

- MGJ
- JMGP
- MGP
- MGPW
- MGQ**
- MGG
- MGC
- MGF
- MGZ
- MGT

**Non-rotating Accuracy of Plate**




For non-rotating accuracy  $\theta$  without load, use a value no more than the values in the table as a guide.

Bore size (mm)	Non-rotating accuracy $\theta$	
	MGQM	MGQL
12	$\pm 0.08^\circ$	$\pm 0.10^\circ$
16		
20	$\pm 0.07^\circ$	$\pm 0.09^\circ$
25		
32	$\pm 0.06^\circ$	$\pm 0.08^\circ$
40		
50	$\pm 0.05^\circ$	$\pm 0.06^\circ$
63		
80	$\pm 0.04^\circ$	$\pm 0.05^\circ$
100		

- D-
- X

## Operating Range when Used as Stopper

### Bore Size $\phi 12$ to $\phi 25$ /MGQM12 to 25 (Slide Bearing)




\* When selecting a model with a longer L dimension, be sure to choose a bore size which is sufficiently large.

#### Caution on handling


Note 1) When using as a stopper, select a model with 30 stroke or less.

Note 2) Model MGQL (Ball bushing bearing) cannot be used as a stopper.

#### MGQM12 to 25 (Slide bearing)



### Bore Size $\phi 32$ to $\phi 100$ /MGQM32 to 100 (Slide Bearing)




\* When selecting a model with a longer L dimension, be sure to choose a bore size which is sufficiently large.

#### Caution on handling

Note 1) When using as a stopper, select a model with 50 stroke or less.

Note 2) Model MGQL (Ball bushing bearing) cannot be used as a stopper.


#### MGQM32 to 100 (Slide bearing)



## Operating Range when Used as Lifter


- Select the bore size so that the total load mass is below the theoretical output (see the table below).

Bore size (mm)	Theoretical output
12, 16	40% or below
20, 25	50% or below
32 to 100	60% or below




### MGQM/Slide bearing

#### MGQM12 to 25-□




### MGQL/Ball bushing bearing


#### MGQL12 to 25-<sup>10</sup>/<sub>20</sub> (10, 20, 30 Stroke)




#### MGQL12 to 25-Over 30 stroke




#### MGQM32 to 100 (Slide bearing)



#### MGQL32 to 100-<sup>25</sup>/<sub>50</sub> (25, 50 stroke)



#### MGQL32 to 100-Over 50 stroke



MGJ

JMGP

MGP

MGPW

**MGQ**

MGG

MGC

MGF

MGZ

MGT


D-□

-X□


# MGQ Series

## Construction/MGQM Series


### MGQM12 to 25



50 stroke or less





ø12, ø16



ø20, ø25 Over 50 stroke

### MGQM32 to 100



Over 50 stroke

### Component Parts

No.	Description	Material	Note
1	Body	Aluminum alloy	Hard anodized
2	Piston	Aluminum alloy	
3	Piston rod	Stainless steel	ø12 to ø25
		Carbon steel	ø32 to ø100 Hard chrome plated
4	Collar	Aluminum bearing alloy	ø12 to ø40 White anodized
		Aluminum alloy casted	ø50 to ø100 Painted
5	Bushing	Bearing alloy	ø50 to ø100
6	Head cover	Aluminum alloy	ø12 to ø63 Chromated
			ø80 to ø100 Painted
7	Guide rod	Carbon steel	Hard chrome plated
8	Plate	Carbon steel	Nickel plated
9	Plate mounting bolt	Carbon steel	Nickel plated
10	Guide bolt	Carbon steel	Nickel plated

No.	Description	Material	Note
11	Retaining ring	Carbon tool steel	Phosphate coated
12	Retaining ring	Carbon tool steel	Phosphate coated
13	Bumper A	Urethane	
14	Bumper B	Urethane	
15	Magnet	—	
16	Slide Bearing	Bearing alloy	
17	Felt	Felt	
18	Holder	Resin	
19	Ball bushing		
20*	Piston seal	NBR	
21*	Rod seal	NBR	
22*	Gasket A	NBR	
23*	Gasket B	NBR	

### Replacement Parts: Seal Kit

Bore size (mm)	Kit no.	Description
12	MGQ12-PS	A set of 20, 21, 22 and 23 listed above
16	MGQ16-PS	
20	MGQ20-PS	
25	MGQ25-PS	
32	MGQ32-PS	

\* Seal kit includes 20 to 23. Order the seal kit, based on each bore size.


Bore size (mm)	Kit no.	Description
40	MGQ40-PS	A set of 20, 21, 22 and 23 listed above
50	MGQ50-PS	
63	MGQ63-PS	
80	MGQ80-PS	
100	MGQ100-PS	

\* Since the seal kit does not include a grease pack, order it separately.  
Grease pack part no.: GR-S-010 (10 g)




**Construction/MGQL Series**


**MGQL12 to 25**



**30 stroke or less**





**ø12, ø16 Over 30 stroke**



**ø20, ø25 Over 30 stroke**

**MGQL32 to 100**



**ø50 or more**


- MGJ
- JMGP
- MGP
- MGPW
- MGQ**
- MGG
- MGC
- MGF
- MGZ
- MGT

- D-□
- X□



# MGQ Series

## Bore Size $\varnothing 12$ to $\varnothing 25$ : MGQM, MGQL



### MGQM, MGQL Common Dimensions

Bore size (mm)	Standard stroke (mm)	B	C	DA	G	GA	GB	H	J	K	L	MM	ML	NN	P			PW	Q	R
															Nil	TN	TF			
12	10, 20, 30, 40,	39	29	6	29	11	7.5	58	16	13	18	M4 x 0.7	10	M4 x 0.7	M5 x 0.8	—	—	7	14	48
16	50, 75, 100	43	33	8	33	11	8	64	18	15	22	M5 x 0.8	13	M5 x 0.8	M5 x 0.8	—	—	5	16	52
20	20, 30, 40, 50, 75, 100	47	37	10	36	10.5	8.5	74	19	17	26	M5 x 0.8	13	M5 x 0.8	Rc1/8	NPT1/8	G1/8	7	18	60
25	125, 150, 175, 200	47.5	37.5	12	42	11.5	9	88	21	21	32	M6 x 1.0	15	M6 x 1.0	Rc1/8	NPT1/8	G1/8	8	26	70

Bore size (mm)	S	T	TA	TB	U	V	W	X	YY	YL	Z
12	22	56	2	5	36	40	5	50	M4 x 0.7	7	12
16	25	62	2.5	5.5	38	42	7	54	M5 x 0.8	8	13
20	30	72	2	4	46	52	10	64	M5 x 0.8	8	13
25	38	86	2	2	56	62	10	76	M6 x 1.0	9	14

### MGQM (Slide bearing)/A, DB, E Dimensions (mm)

Bore size (mm)	A		DB	E	
	50 st or less	Over 50 st		50 st or less	Over 50 st
12	39		8	0	
16	43		10	0	
20	47	61.5	12	0	14.5
25	47.5	62	16	0	14.5

### MGQL (Ball bushing bearing)/A, DB, E Dimensions (mm)


Bore size (mm)	A		DB	E	
	30 st or less	Over 30 st		30 st or less	Over 30 st
12	43	55	6	4	16
16	49	65	8	6	22
20	57	74	10	10	27
25	63.5	79.5	13	16	32

Note) For intermediate strokes other than standard strokes, refer to the Manufacture of Intermediate Stroke on page 521.

• Bore size 12 and 16 are only for the M5 x 0.8 port.

• For bore size 20 or more, Rc, NPT and G ports can be selected. (Refer to page 520.)

## Bore Size $\phi 32$ to $\phi 100$ : MGQM, MGQL



### MGQM, MGQL Common Dimensions

Bore size (mm)	Standard stroke (mm)	B	C	DA	F	G	GA	GB	H	J	K	L	MM	ML	NN	P			PW	Q	R	S
																Nil	TN	TF				
32	25, 50, 75, 100, 125, 150, 175, 200	47.5	37.5	16	8	51	12.5	9	114	25	26	38	M8 x 1.25	20	M8 x 1.25	Rc1/8	NPT1/8	G1/8	15	30	96	48
40		54	44	16	8	51	14	10	124	25	26	38	M8 x 1.25	20	M8 x 1.25	Rc1/8	NPT1/8	G1/8	21	30	106	48
50		56	44	20	10	59	14	11	140	29	30	44	M10 x 1.5	25	M10 x 1.5	Rc1/4	NPT1/4	G1/4	27	40	120	56
63		61	49	20	10	72	16.5	13.5	150	35.5	36.5	44	M10 x 1.5	25	M10 x 1.5	Rc1/4	NPT1/4	G1/4	33	50	130	69
80		74.5	56.5	25	16	92	19	15.5	188	45.5	46.5	56	M12 x 1.75	30	M12 x 1.75	Rc3/8	NPT3/8	G3/8	37	60	160	88
100	84	66	30	16	112	23	19	224	55.5	56.5	62	M14 x 2	35	M14 x 2	Rc3/8	NPT3/8	G3/8	40	80	190	108	

Bore size (mm)	T	TA	TB	V	W	X	YY	YL	Z
32	112	2	1	80	5	100	M8 x 1.25	11	16
40	122	2	1	90	10	110	M8 x 1.25	11	17
50	138	2	1	100	10	124	M10 x 1.5	12.5	17
63	148	2	1	110	10	132	M10 x 1.5	15	19
80	185	2.5	1.5	140	15	166	M12 x 1.75	18	21
100	221	2.5	1.5	170	15	200	M14 x 2	21	25

### MGQM (Slide bearing)/ A, DB, E Dimensions

Bore size (mm)	A			DB	E
	50 st or less	Over 50 st			
32	71.5	20	24		
40	71.5	20	17.5		
50	81	25	25		
63	81	25	20		
80	93	28	18.5		
100	105	36	21		

### MGQL (Ball bushing bearing)/ A, DB, E Dimensions

Bore size (mm)	A		DB	E	
	50 st or less	Over 50 st		50 st or less	Over 50 st
32	53	90	16	5.5	42.5
40	54	90	16	0	36
50	60	102	20	4	46
63	61	102	20	0	41
80	84	143	25	9.5	68.5
100	89	153	30	5	69

Note) For intermediate strokes other than standard strokes, refer to the Manufacture of Intermediate Stroke on page 521.


• Rc, NPT and G ports can be selected. (Refer to page 520.)

### Grooves (Except $\phi 12$ , $\phi 16$ , $\phi 20$ , $\phi 25$ )

Use grooves section "a" and section "b" in the figure below of the cylinder body for firmly fixing in the following case. (Applicable bolt size is M3.)

• These grooves can be used for firmly fixing the tying bands of lead wires of the auto switch, etc., and also terminal boards, etc., to the main body of the cylinder.

• When the terminal block is fixed on a cylinder directly.



# Auto Switch Mounting

## Minimum Stroke for Auto Switch


		(mm)									
Auto switch model	No. of auto switches mounted	ø12	ø16	ø20	ø25	ø32	ø40	ø50	ø63	ø80	ø100
D-A9□	1 pc.	5 (Note 1)					5				
	2 pcs.	10 (Note 1)					10				
D-A9□V D-M9□V	1 pc.						5				
	2 pcs.						10				
D-M9□	1 pc.	5 (Note 1)						5			
	2 pcs.	10 (Note 1)				10					
D-M9□W	1 pc.						5 (Note 2)				
	2 pcs.	10 (Note 2)					10				
D-M9□WV D-M9□AV	1 pc.						5 (Note 2)				
	2 pcs.						10				
D-M9□A	1 pc.						5 (Note 2)				
	2 pcs.						10 (Note 2)				
D-Z7□ D-Z80 D-Y59□ D-Y7P	1 pc.	5 (Note 1)							5		
	2 pcs.	10 (Note 1)						10			
D-Y69□ D-Y7PV	1 pc.						5				
	2 pcs.						5				
D-Y7□W D-Y7□WV D-Y7BA	1 pc.						5 (Note 2)				
	2 pcs.						10 (Note 2)				

Note 1) Confirm that it is possible to secure the bending radius of 10 mm of the auto switch lead wire before use.

Note 2) Confirm that it is possible to securely set the auto switch(es) within the range of indicator green light ON range before use.

For in-line entry type, please also consider Note 1) shown above.

## Auto Switch Proper Mounting Position (Detection at Stroke End)



## Auto Switch Proper Mounting Position (mm)

Auto switch model	D-M9□ D-M9□V D-M9□W D-M9□WV D-M9□A D-M9□AV		D-A9□ D-A9□V		D-Z7□/Z80 D-Y59□/Y7P D-Y69□/Y7PV D-Y7□W D-Y7□WV D-Y7BA	
	A	B	A	B	A	B
12	6	8	2	4	1	3
16	9	9	5	5	4	4
20	9.5	12.5	5.5	8.5	4.5	7.5
25	9.5	13	5.5	9	4.5	8
32	10.5	12	6.5	8	5.5	7
40	14.5	14.5	10.5	10.5	9.5	9.5
50	12.5	16.5	8.5	12.5	7.5	11.5
63	15	19	11	15	10	14
80	18	23.5	14	19.5	13	18.5
100	22.5	28.5	18.5	24.5	17.5	23.5

Note) Adjust the auto switch after confirming the operating conditions in the actual setting.

## Auto Switch Mounting Height (mm)

Auto switch model	D-A9□ D-M9□ D-M9□W D-M9□A D-Z7□ D-Z80 D-Y59□ D-Y7P D-Y7□W D-Y7BA	D-A9□V	D-M9□V D-M9□WV D-M9□AV	D-Y69□ D-Y7PV D-Y7□WV	
					Hs
12		16	18.5	20.5	17
16		18.5	21	23	19.5
20		19.5	22.5	24.5	20.5
25		21	23.5	26	22
32		24.5	27	28.5	25.5
40		24	26	27.5	25
50		28	30	31.5	29
63		34.5	36.5	39.5	35.5
80		44	46.5	48.5	45
100		52	54	56	52.5

## Operating Range


Auto switch model	Bore size (mm)									
	12	16	20	25	32	40	50	63	80	100
<b>D-A9□/A9□V</b>	7	9.5	9	9	9	9	9	10.5	10	10.5
<b>D-M9□/M9□V</b> <b>D-M9□W/M9□WV</b>	4	5.5	5	5	5.5	5	5.5	5.5	6.5	7
<b>D-Z7□/Z80</b> <b>D-Y5□□/Y6□□/Y7□□</b>	5	6	6	6.5	8.5	8.5	9	10	10	11.5

Since the operating range is provided as a guideline including hysteresis, it cannot be guaranteed (assuming approximately ±30% dispersion). It may vary substantially depending on an ambient environment.

## Auto Switch Mounting Bracket: Part No.

Auto switch model	Bore size (mm)
	ø12 to ø100
<b>D-A9□/A9□V</b> <b>D-M9□/M9□V</b> <b>D-M9□W/M9□WV</b>	BMG2-012

**D-A9□(V)/M9□(V)/M9□W(V)**



Other than the applicable auto switches listed in “How to Order”, the following auto switches can be mounted. For detailed specifications, refer to pages 1119 to 1245.

Auto switch type	Model	Electrical entry (Fetching direction)	Features
<b>Reed</b>	D-Z73, Z76	Grommet (In-line)	—
	D-Z80		Without indicator light
<b>Solid state</b>	D-Y69A, Y69B, Y7PV	Grommet (Perpendicular)	—
	D-Y7NWV, Y7PWV, Y7BWV		Diagnostic indication (2-color indicator)
	D-Y59A, Y59B, Y7P	Grommet (In-line)	—
	D-Y7NW, Y7PW, Y7BW		Diagnostic indication (2-color indicator)
	D-Y7BA		Water resistant (2-color indicator)

\* For solid state auto switches, auto switches with a pre-wired connector are also available. Refer to pages 1192 and 1193 for details.

\* Normally closed (NC = b contact), solid state auto switch (D-F9G/F9H/Y7G/Y7H type) are also available. For details, refer to pages 1137 and 1139.

MGJ

JMGP

MGP

MGPW

**MGQ**

MGG

MGC

MGF

MGZ

MGT

D-□

-X□

# MGQ Series

# Made to Order: Individual Specifications

Please contact SMC for detailed dimensions, specifications and lead times.



## 1 Helical Insert Thread Specifications

Symbol  
**-X168**


MGQ<sup>M</sup><sub>L</sub> [Bore size] — [Stroke] — [Auto switch type] [Lead wire length] [No. of auto switches] —X168

Helical insert thread specifications

Mounting thread type has been changed to the helical insert thread type.

### Specifications

Bearing type	Slide bearing	Ball bushing bearing
Series	<b>MGQM</b>	<b>MGQL</b>
<b>Bore size (mm)</b>	32, 40, 50, 63, 80, 100	
<b>Lubrication</b>	Non-lube	
<b>Auto switch</b>	Mountable	



Bore size (mm)	MM	ML	YY	YL
<b>32</b>	M6 x 1.0	12	M6 x 1.0	9
<b>40</b>	M6 x 1.0	12	M6 x 1.0	9
<b>50</b>	M8 x 1.25	16	M8 x 1.25	12
<b>63</b>	M8 x 1.25	16	M8 x 1.25	12
<b>80</b>	M10 x 1.5	20	M10 x 1.5	15
<b>100</b>	M12 x 1.75	24	M12 x 1.75	18

Note) Other dimensions are the same as standard type.


## 2 Bottom Mounting Type (MGQM type is only available.)

Symbol  
**-X367**

MGQ M [32] — [ ] — [50] — [ ] — [ ] —X367

Compact guide cylinder  
Bearing type  
M | Slide bearing  
Bore size (mm)  
20 | 20 mm  
25 | 25 mm  
32 | 32 mm  
40 | 40 mm  
50 | 50 mm  
63 | 63 mm  
80 | 80 mm  
100 | 100 mm  
Port thread type  
Cylinder stroke (mm)  
Bore size (mm) | Applicable stroke (mm)  
20 to 25 | 75, 100  
32 to 100 | 25, 50, 75, 100  
Auto switch  
Suffix for auto switch  
Bottom mounting type

Because the guide rods do not protrude from the bottom surface of the body, it is not necessary to machine relief holes for the guide rods.



Note) Full length dimension of bushing for guide rod (ZZ) is shorter than the standard type.


**3 Long Bushing Type (MGQL type is only available.)**

Symbol  
**-X399**

MGQL  Bore size  Stroke  Auto switch type  Lead wire length  No. of auto switches  -X399

ø32 to ø100/MGQL-X399: Long bushing type

Long bushing type



(mm)

Bore (mm)	Applicable stroke	A	B	C	E	W
32	5, 10, 15, 20, 25, 30, 40, 50	165	122.5	112.5	42.5	80
40		165	129	119	36	85
50		177	131	119	46	85
63		177	136	124	41	85
80		218	149.5	131.5	68.5	90
100		228	159	141	69	90

Note 1) Dimensions are the same as for standard type of 75 stroke.

Note 2) Applicable stroke is available at 5 mm intervals and the spacer is installed inside.

Note 3) Ball bushing bearing type with 50 stroke or less is twice as long as the normal bearing length to strengthen the guide.

**4 Magnetic Field Resistant Auto Switch (D-P4DW)**

Symbol  
**-X563**


MGQ<sup>M</sup><sub>L</sub>  Bore size  Stroke  P4DW  Lead wire length  No. of auto switches  -X563

Magnetic field resistant auto switch (D-P4DW)

**Specifications**

Bearing type	Slide bearing	Ball bushing bearing
Series	<b>MGQM</b>	<b>MGQL</b>
Bore size (mm)	40, 50, 63, 80, 100	
Lubrication	Non-lube	
Auto switch	Mountable	

Note) For 25, 50 stroke, the number of available auto switch is 1 pc.



(mm)

Bore size (mm)	Hs	Ht
40	31.5	30.1
50	35.0	34.7
63	42.5	36.1
80	53.5	38.7
100	60.5	45.1

MGJ

JMGP

MGP

MGPW

MGQ

MGG

MGC

MGF

MGZ

MGT

D-□

-X□