



嵌入式接头 KF系列



特点：采用旋转锁母，能防止软管脱落。

基本材料：铜

最高使用压力：1.0MPa

可用于真空系统（真空度101kPa以下）










适合软管材料：尼龙及PU软管

任选项：

S—带密封剂

例如：KFL08U-01S

型号选择表

类型	连接 T	适合软管外径/内径 ϕd (mm)							
		$\phi 4/2.5$	$\phi 6/4$	$\phi 8/5$	$\phi 8/6$	$\phi 10/6.5$	$\phi 10/7.5$	$\phi 12/8$	$\phi 12/9$
直通接头：KFH 	1/8	KFH04-01	KFH06-01	KFH08U-01	KFH08N-01				
	1/4	KFH04-02	KFH06-02	KFH08U-02	KFH08N-02	KFH10U-02	KFH10N-02	KFH12U-02	KFH12N-02
	3/8		KFH06-03	KFH08U-03	KFH08N-03	KFH10U-03	KFH10N-03	KFH12U-03	KFH12N-03
	1/2					KFH10U-04	KFH10N-04	KFH12U-04	KFH12N-04
弯头：KFL 	1/8	KFL04-01	KFL06-01	KFL08U-01	KFL08N-01				
	1/4	KFL04-02	KFL06-02	KFL08U-02	KFL08N-02	KFL10U-02	KFL10N-02	KFL12U-02	KFL12N-02
	3/8		KFL06-03	KFL08U-03	KFL08N-03	KFL10U-03	KFL10N-03	KFL12U-03	KFL12N-03
	1/2					KFL10U-04	KFL10N-04	KFL12U-04	KFL12N-04
直通接管：KFH 	-	KFH04-00	KFH06-00	KFH08U-00	KFH08N-00	KFH10U-00	KFH10N-00	KFH12U-00	KFH12N-00
T形接头：KFT 	1/8	KFT04-01	KFT06-01	KFT08U-01	KFT08N-01				
	1/4	KFT04-02	KFT06-02	KFT08U-02	KFT08N-02	KFT10U-02	KFT10N-02	KFT12U-02	KFT12N-02
	3/8		KFT06-03	KFT08U-03	KFT08N-03	KFT10U-03	KFT10N-03	KFT12U-03	KFT12N-03
	1/2					KFT10U-04	KFT10N-04	KFT12U-04	KFT12N-04
T形接管：KFT 	-	KFT04-00	KFT06-00	KFT08U-00	KFT08N-00	KFT10U-00	KFT10N-00	KFT12U-00	KFT12N-00
检测用T形接头：KFY 	1/8	KFY04-01	KFY06-01	KFY08U-01	KFY08N-01				
	1/4	KFY04-02	KFY06-02	KFY08U-02	KFY08N-02	KFY10U-02	KFY10N-02	KFY12U-02	KFY12N-02
	3/8		KFY06-03	KFY08U-03	KFY08N-03	KFY10U-03	KFY10N-03	KFY12U-03	KFY12N-03
	1/2					KFY10U-04	KFY10N-04	KFY12U-04	KFY12N-04
隔板安装接管：KFE 	-	KFE04-00	KFE06-00	KFE08U-00	KFE08N-00	KFE10U-00	KFE10N-00	KFE12U-00	KFE12N-00
隔板安装内螺纹接头：KFE 	1/4		KFE06-02						
	3/8			KFE08U-03	KFE08N-03	KFE10U-03	KFE10N-03	KFE12U-03	KFE12N-03
内螺纹接头：KFF 	1/4	KFF04-02	KFF06-02	KFF08U-02	KFF08N-02	KFF10U-02	KFF10N-02	KFF12U-02	KFF12N-02
	3/8		KFF06-03						

注：尚有铰接型弯头 (KFV系列)，铰接型长弯头(KFW系列)及堵头(KFP系列)，可联络 SMC 营业员。