



难燃性快换接头 KR系列

(符合美国 UL-94 标准V-O)



特点：防火花设计，适用于焊接工业

基本材料：铜

使用流体：空气及水




最高使用压力：1.0MPa

环境及流体温度：0~60℃(水)、-5~60℃(空气)

标准型带密封剂

适合软管：FR 系列难燃性软尼龙管

型号选择表

类型	连接 T	适合软管外径 ϕd (mm)			
		$\phi 6$	$\phi 8$	$\phi 10$	$\phi 12$
直通接头：KRH 	1/8	KRH06-01S	KRH08-01S	KRH10-01S	
	1/4	KRH06-02S	KRH08-02S	KRH10-02S	KRH12-02S
	3/8	KRH06-03S	KRH08-03S	KRH10-03S	KRH12-03S
	1/2			KRH10-04S	KRH12-04S
弯头：KRL 	1/8	KRL06-01S	KRL08-01S	KRL10-01S	
	1/4	KRL06-02S	KRL08-02S	KRL10-02S	KRL12-02S
	3/8	KRL06-03S	KRL08-03S	KRL10-03S	KRL12-03S
	1/2			KRL10-04S	KRL12-04S
直通接管：KRH 	-	KRH06-00	KRH08-00	KRH10-00	KRH12-00
弯管：KRL 	-	KRL06-00	KRL08-00	KRL10-00	KRL12-00
T形接头：KRT 	1/8	KRT06-01S	KRT08-01S	KRT10-01S	
	1/4	KRT06-02S	KRT08-02S	KRT10-02S	KRT12-02S
	3/8	KRT06-03S	KRT08-03S	KRT10-03S	KRT12-03S
	1/2			KRT10-04S	KRT12-04S
T形接管：KRT 	-	KRT06-00	KRT08-00	KRT10-00	KRT12-00
检测用T形接头：KRY 	1/8	KRY06-01S	KRY08-01S	KRY10-01S	
	1/4	KRY06-02S	KRY08-02S	KRY10-02S	KRY12-02S
	3/8	KRY06-03S	KRY08-03S	KRY10-03S	KRY12-03S
	1/2			KRY10-04S	KRY12-04S
插杆减径接管：KRR 	$\phi 8$	KRR06-08			
	$\phi 10$	KRR06-10	KRR08-10		
	$\phi 12$		KRR08-12	KRR10-12	
隔板安装直通接管：KRE 	-	KRE06-00	KRE08-00	KRE10-00	KRE12-00
堵头：KRP 	-	KRP-06	KRP-08	KRP-10	KRP-12

注：尚有45°弯头(KRK)、万向弯头(KRV)、长弯头(KRW)、Y形接管(KRU)、Y形接头(KRU)、插杆Y形接管(KRU)及防燃盖(KR)，可联络SMC营业员。