








系列	外形图	名称	连接口径	有效截面积mm ²	Cv 值	特点	产品样本
VK300		3通直动式电磁阀 座阀结构,弹性密封	M5 × 0.8 1/8	4	0.2	直接配管· 底板配管 N.C., N.O., C.O.	Best Pneumatics 2004 Vol.4
VZ ¹ / ₅ 300		3通电磁阀 弹性密封	M5 × 0.8 1/8 · 1/4	0.55 ~ 13.5	0.023 ~ 0.68	直接配管· 底板配管 N.C., N.O.	Best Pneumatics 2004 Vol.4
VZ ² / ₄ 00		3通先导式电磁阀 间隙密封	M5 × 0.8 Rc1/8 · 1/4	2.6 ~ 11	0.13 ~ 0.53	直接配管· 底板配管 N.C., N.O.	Best Pneumatics 2004 Vol.4
SX ³ / ₇ 000		5通先导式电磁阀 弹性密封	M5 × 0.8 1/8 · 1/4 · 3/8 C4 · C6 · C8 · C10	3 ~ 25	0.16 ~ 1.2	先导阀集中于一侧。 低功率0.6W。响应快。 寿命长。与SY系列 底板共用	Best Pneumatics 2004 Vol.1
EVS ⁰¹ / ₀₂		5通先导式电磁阀 弹性密封 间隙密封	1/8 · 1/4	6.5 ~ 22	0.2 ~ 1.0	底板接口尺寸 符合ISO标准。 电接头为M12 或M8接头	Best Pneumatics 2004 Vol.5
EVS ⁶ / ₈ 10			1/4 ~ 1	20.5 ~ 80	0.9 ~ 4		
VZS ² / ₃ 000		5通先导式电磁阀 间隙密封 插入式及非插入式底板	Rc1/8 · 1/4	6.3 ~ 13.2	0.35 ~ 0.73	最大动作频率 20Hz	Best Pneumatics 2004 Vol.3
VZ ¹ / ₅ 3000		4·5通先导式电磁阀 弹性密封	M5 × 0.8 Rc1/8 C4 · C6 · C8	0.6 ~ 14.5	0.035 ~ 0.78	直接配管· 底板配管	Best Pneumatics 2004 Vol.3
VZA ² / ₄ 000		5通气控阀 弹性密封	M5 × 0.8 Rc1/8 · 1/4	3 ~ 12	0.15 ~ 0.56	直接配管· 底板配管	Best Pneumatics 2004 Vol.5