






智能伺服马达单元 MTR-DCI

附件

FESTO

订货数据 - 电缆				
	简要说明	电缆长度	订货号	型号
	电源电缆 引脚分配 → 6/2.2-7	2.5 m	537 931	KPWR-MC-1-SUB-9HC-2,5
		5 m	537 932	KPWR-MC-1-SUB-9HC-5
		10 m	537 933	KPWR-MC-1-SUB-9HC-10
	控制电缆，用于将 I/O 连接至任意 PLC 控制器 引脚分配 → 6/2.2-7	2.5 m	537 923	KES-MC-1-SUB-9-2,5
		5 m	537 924	KES-MC-1-SUB-9-5
		10 m	537 925	KES-MC-1-SUB-9-10
	编程电缆 用于使用 FCT 软件通过 RS232 接口进行参数设置和调试 引脚分配 → 6/2.2-7	2.5 m	537 926	KDI-MC-M8-SUB-9-2,5

订货数据 - 插头				
	简要说明	订货号	型号	
现场总线适配器，用于 Profibus				
	<ul style="list-style-type: none"> - 9 针 Sub-D 插头转接至 5 针圆形 M12 插头/插座，加上用于逻辑电源的圆形 M12 插头 - 总线终端电阻必须外部连接 	537 934	FBA-PB-SUB-9-3XM12	
现场总线适配器，用于 CANopen 和 DeviceNet				
	<ul style="list-style-type: none"> - 9 针 Sub-D 插头转接至 5 针圆形 M12 插头 - 总线终端电阻必须外部连接 	540 324	FBA-CO-SUB-9-M12	